



KALOGEROPOULOS S.A.

WMF-2, First edition

**HEADQUARTERS:** 35 Gounari str, Piraeus 18531, Greece, **Tel.:** +30 210 412 4518, **Fax:** +30 210 410 1607  
**PLANT:** Industrial Park, Building Block 11, Aspropyrgos 19300, Greece,  
**Tel.:** +30 210 557 4464, **Fax:** +30 210 557 4499, **Mob.:** 697 686 9781,  
**E-mail:** info@kalochem.gr, **Website:** www.kalochem.gr

## TEAK OIL KL



### FEATURES

- ▲ High performance oil for wood TEAK that restores color and maintains it.
- ▲ **Appearance:** light brown liquid with odor similar to hydrocarbon, immiscible with water.

### DIRECTIONS FOR USE

- ▲ Rub wooden surfaces to become clean and smooth. With a brush apply the product onto TEAK wood and let it dry. Repeat this process as many times as required.

### HANDLING

- ▲ To product is harmful. If swallowed, do not induce vomiting, seek medical advice immediately and show the container or label. Wear suitable protective gloves, clothing and eye protection. Ensure good ventilation at the workplace.

### PACKAGING

- ▲ Available in 1lt, 4lt and 20lt plastic containers.

### STORAGE

- ▲ Store in a cool, dry place away from sunlight in tightly closed containers. Store separately from food items, beverages and feed.