

## PRODUCT DATA SHEET

**RAJ GROUP** 

## RAJWAX – PARAFFIN WAX

Product Description: RAJWAX ® PARAFFIN WAX is Hydrocarbon Wax, suitable for Pharmaceutical, Cosmetic and Food industries.

Purity Status: RAJWAX – Paraffin WAX is manufactured in compliance with IP / BP/Ph.Eur. and conforms to the requirements of US FDA 21CFR 172.886

	Test Description	Test Method	Specification	Typical Values
ieristics	Description	IP	White translucent pellets / slabs, frequently showing a crystalline structure; odorless even when freshly cut; slightly greasy to the touch. When melted, the liquid is free from fluorescence by daylight.	White translucent pellets / slabs, frequently showing a crystalline structure; odorless even when freshly cut; slightly greasy to the touch. When melted, the liquid is free from fluorescence by daylight.
Typical Properties & Characteristics	Colour (Saybolt)	ASTM D 156	Min +20	+28
	Drop Melting point, <sup>0</sup> C	<b>ASTM D 127</b>	58 - 63	59.5
	Congealing Range/Congealing point, °C	IP/Ph.Eur / NF.	50 - 65	58.0
	Acidity / Alkalinity	IP	To Pass	Passes
	Melting point, °C (Cooling curve)	ASTM D 87	52 - 62	57.0
	Oil Content, %	ASTM D721	0.5 (max)	0.12
	Needle Pen No. @ 25 °C, dmm	ASTM D 1321	Max 15	10 dmm
	Sulphated Ash	IP	0.1% Max	Nil
	Sulphates	BP / Ph.Eur.	< 150 ppm	10 ppm
	Ulltra Violet absorbance Test	IS 4654	To Pass	Passes
	Polycyclic Aromatic Hydrocarbon	BP / Ph.Eur.	To Pass	Passes
	UV absorbance per cm pathlength	FDA 21 CFR 172.886	To Pass	Passes
	Packaging	Paraffin WAX	is offered in 25 Kg net Carto	n Boxes.

Product Form &	: RAJWAX – Paraffin WAX is offered in 25 Kg net Carton Boxes.		
Packaging			
Health & Safety	: See corresponding product MSDS		
Offices	Raj Petro Specialities Pvt. Ltd.,		
	2 <sup>nd</sup> Floor, "DOSHI TOWERS",		
	156, Poonamallee High Road,		
	Kilpauk, Chennai – 600 010.		
	Ph: (91)-44-42288900 to 42288910		
	Fax: +91-44-42288912		
	E-mail: marketing rl@rajgrp.com		
Website	www.rajgrp.com		

## Note:

- The above data is indicative of recent average Values only. Minor variations which do not affect product performance or quality may be expected in manufacture.
- Specific requirements can be custom-made on request.
- The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.